FEMTO X

1.185

Allowed user weight

**130 kg*

Suitable for passenger transport



MEYRA GROUP



Two front frame angles



Precise castor adjustment



Parallel folding



Back angle adjustment

FUSE Together

EFFICIENCY

- Permanent provision with adjustment possibilities to functional changes reduces follow-up costs
- Extensive serial equipment minimises necessity for expensive customised parts
- Little wear and proneness to repair through integral design of the frame and the quality of the attachment components

THERAPEUTIC BENEFIT

- Perfect easy running and little own weight support the independence of the user
- *Anpassbar an Funktionsveränderungen und individuelle Bedürfnisse des Anwenders durch feinstufige Einstellung von Rückenteil, Sitz und Fahrwerk
- Extensive equipment assortment for long-term users
- Compact sitting, driving and transport through the optimal frame design
- Adjustable seat and back strap, individually adjustable back height
- Optimum mobility traits: lighter, sportier, easier to tilt and turn

FIELD OF USE

- For permanent and long term provision
- For paraplegic provision
- Very good suitability for many disease patterns, even for severely encumbered
- Users without function of the lower extremities (lateral transfer, driven through the handrims)
- For very active wheelchair users, handbikers and frequent travellers

● ORDER ○ COST ESTIMATE ○ CUSTOM DESIGN

Please send the order form by e-mail to: info@meyragroup.com **Customer service:** +49 571 93292 555

Billing address / Customer ref. no.:

Delivery address:

Tax-ID

Consignment / Comments:

Order quantity:

MEYRA



Standard configuration

- Standard front frame
- Without taper frame
- Plastic castor
- Aluminum rear wheel
- Camber 0°
- High-pressure tires
- Stainless steel push rims
- Pressure brake (push to lock)
- Backrest Angle
- Black textile backrest cover
- Push handle short
- Plastic side guard
- Plastic base plates
- Frame Colours

Allowed user weight

*130 kg

Suitable for passenger transport

Hints

You can find information on the measurement process at www.meyra.de/messverfahren

Valid from 01.11.2026.
*Irrtümer, Druckfehler und Änderungen vorbehalten.

Use our K.I.S.S.S. for orders and configurations at www.kisss-by-meyra.de
You avoid queries and incorrect orders thanks to the buildability check

ACTIVE

Technical specifications

Seat widths in mm	*320 - 520 in 20mm Schritten
Width ready to drive in mm from	Seat width + 180
Width folded in mm from	*290 bei Radsturz 1° / 330 bei Radsturz 3°
Seat depth in mm	*340 - 500 in 20mm Schritten
Seat height front/rear in mm	425 bis 560 / 390 bis 530
Overall height in mm	Rear seat height + back support height
Back support height in mm	*Von 250 bis 500 verstellbar in 15mm Schritte
Arm support height in mm	*ca. 170 - 245
Length with footrest in mm	790 - 1130 (depending on frame length, wheel size and axle position)
User weight	*130 kg
Empty weight from	9,5 kg
Permitted total weight in kg	145 kg
Transport weight	*7,4 kg
Rear wheel	*600 mm (24") / 635 mm (25") / 660 mm (26")
Brake test according to STANDARD	7°
Backrest Angle	Adjustable as standard -10°/-5°/0°/+5°/+10°

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

01 *Rahmen

	CODE	DESCRIPTION	*WINKEL
❑	346	Standard front frame (straight tubes, not tapered)	70°
❑	347	Compact front frame (straight tubes, not tapered)	80°

Frame Colours

	CODE	DESCRIPTION
❑	130	Titanium grey
❑	206	Matt black
❑	224	Blue metallic
❑	227	*Redmetallic
❑	4044	*Redmetallic Matt
❑	4049	Olive green matt
❑	4050	Sky blue
❑	4051	Chalk
❑	4919	Silverline
❑	4922	Metallic green

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

02 Seat Width (SW) / Seat Depth (SD)

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Seat depth is measured from the front of the backrest tube to the front edge of the seat upholstery.

		C-394	C-366	C-368	C-615	C-784	C-618	C-619	C-787	C-792
		SD 340mm	SD 360mm	SD 380mm	SD 400mm	SD 420mm	SD 440mm	SD 460mm	SD 480mm	SD 500mm
C-32	SW 320mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-34	SW 340mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-36	SW 360mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-38	SW 380mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-40	SW 400mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-342	SW 420mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-344	SW 440mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-46	SW 460mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-48	SW 480mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-350	SW 500mm	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-952	SW 520mm	❑	❑	❑	❑	❑	❑	❑	❑	❑

Composite Castor Wheels

The maximum allowable difference between the front and rear seat heights is 100mm.

		Front Seat Height (FSH) in mm												
	Composite Castor Wheels	440	450	460	470	480	490	500	510	520	530	540	550	560
C-2480	4" (100x23mm) with integrated lighting	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-151/908	4" (100x32mm) solid rubber black (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-151/909	4" (100x32mm) solid rubber grey (250g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
C-325/908	5" (125x40mm) solid rubber black (388g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-325/909	5" (125x30mm) solid rubber grey (318g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-327/908	5.5" (142x36mm) soft solid rubber black (570g)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-327/909	5.5" (142x36mm) soft solid rubber grey (570g)				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Aluminium Castor Wheels (32mm)

		Front Seat Height (FSH) in mm											
	Aluminium Castor Wheels (32mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2481	4" (100x32mm) aluminium silver (281g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2482	5" (125x32mm) aluminium silver (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Aluminium Castor Wheels (37mm)

		Front Seat Height (FSH) in mm											
	Aluminium Castor Wheels (37mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2483	4" (100x37mm) silver (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2484	4" (100x37mm) black (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2485	4" (100x37mm) white (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2486	4" (100x37mm) red (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2487	4" (100x37mm) blue (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2488	4" (100x37mm) orange (210g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2489	5" (125x37mm) silver (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2490	5" (125x37mm) black (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2491	5" (125x37mm) white (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2492	5" (125x37mm) red (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2493	5" (125x37mm) blue (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
C-2494	5" (125x37mm) orange (363g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

Carbon Castor Wheels (30mm)

		Front Seat Height (FSH) in mm											
	Carbon Castor Wheels (30mm)	**440**	**450**	**460**	**470**	**480**	**490**	**500**	**510**	**520**	**530**	**540**	**550**
C-2495	4" (100x30mm) black (158g)	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C-2496	5" (125x30mm) black (205g)		❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

04 Rear Wheels / Rear Seat Height (RSH)

The maximum allowable difference between the front and rear seat heights is 100mm.

Rear Wheels (incl. Tyres and Push Rims)

Weight is indicated per complete wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	*HSH	DESCRIPTION	Ø	WEIGHT
❑	752	A	Light-Wheel Schwalbe RightRun Light tyres (1" tyre width) Aluminium push rims, black	24"	
❑	2473	A	Blacklight wheel, aluminium, rim/hub/spokes black Schwalbe Marathon Plus tyres (1" width) Aluminium push rims, black	24"	
❑	2466	A	Cross wheel Knobby tyres (1.75" width) Stainless steel push rims	24"	
❑	2461	A	DayLite wheel, aluminium, rim/hub/spokes black Gazelle tyres (1" width) Aluminium push rims, black ⚠ *Maximum user weight 100kg*	24"	
❑	2468	B	DayLite wheel, aluminium, rim/hub/spokes black Speedlite tyres (1" width) Aluminium push rims, black ⚠ *Maximum user weight 100kg*	25"	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Rear Wheels (without Tyres and Push Rims)

Tyres and push rims must be selected separately. Weight is indicated per wheel (without quick release axle).

RSH (mm)	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530
A	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑		
B			❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	
C				❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑

	CODE	*HSH	DESCRIPTION	Ø	WEIGHT
❑	651	A	Standard wheels, grey	24"	1465g
❑	2651	A	Standard wheels, black	24"	1465g
❑	706	A	Drum brake wheels, 36 radial spokes (stainless steel), drum brake for attendant *Only with push handles, long (C-410) or height-adjustable (C-502)* *NC with light pressure brake (C-2595)* *NC with 3° camber (C-447)*	24"	
❑	848	A	Silverdesign, radial spokes, and high-flange hub	24"	870g
❑	695	A	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *NC with PU tyres, puncture-proof (C-474)* *NC with Carbolife push rims (C-849, C-850, C-853)*	24"	
❑	695	B	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	25"	
❑	695	C	Active wheels, radial spokes, hollow-chamber rim (Jumbo), and high-flange hub, black *Recommended for users from 100kg or for dynamic driving style* *Only with stainless steel (C-493) or titanium (C-445) push rims*	26"	
❑	2470	A	Spinergy LX, rim/hub and 12x4mm spokes black *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2471	A	Spinergy LX, rim/hub black, 12x4mm spokes white *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2472	A	Spinergy LX, rim/hub black, 12x4mm spokes orange *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	687g
❑	2469	A	Spinergy CLX, carbon rim, hub/18x3mm spokes black *NC with PU tyres, puncture-proof (C-474, C-902)*	24"	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

05 Tyres

Tyres are made of a rubber compound that may leave permanent or hard-to-remove marks on certain surfaces (plastic, wood, parquet, carpets or rugs). No liability is accepted for abrasion damage. Weight is indicated per tyre.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	496	High-pressure tyre, 8 bar, 1" tyre width	24"	
❑	486	Pneumatic tyre, grooved tread, 4 bar, 1 3/8" tyre width	24"	
❑	902	PU tyre, puncture-proof, 1" tyre width, grey ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	474	PU tyre, puncture-proof, 1" tyre width, black ⚠ *NC with Active wheel (C-695)* *NC with Spinergy (C-2469, C-2470, C-2471, C-2472)*	24"	
❑	897	Schwalbe Marathon Plus, puncture-resistant, 1" tyre width, black	24"/25"/26"	500g
❑	363	Schwalbe One, puncture-resistant, 1" tyre width, black	24"	
❑	395	Maxxis VN Master Alpha Protect, 10 bar, puncture-resistant, 1" tyre width, black	24"/25"/26"	

06 Push Rims

Weight is indicated per push rim.

	CODE	DESCRIPTION	Ø	WEIGHT
❑	494	Aluminium, silver anodised ⚠ *NC with Active wheel (C-695)*	24"	344g
❑	487	Aluminium, black anodised	24"	255g
❑	493	Stainless steel, polished	24"/25"/26"	
❑	445	Titanium ⚠ *NC with Silverdesign (C-848)* *NC with standard wheels (C-651, C-2651)*	24"/25"/26"	364g (24")
❑	168	Optigripp-special push rim for tetraplegics	24"	
❑	849	Curve L, aluminium, black anodised, ergonomic profile ⚠ *NC with Active wheel (C-695)*	24"	
❑	850	Curve L Tetra-Grip, aluminium, black, ergonomic profile with anti-slip coating ⚠ *NC with Active wheel (C-695)*	24"	
❑	853	Gekko, aluminium, black anodised, ergonomic profile with integrated, replaceable silicone lip ⚠ *NC with Active wheel (C-695)*	24"	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
(S) Special construction/individual solution o.r. - on request

Push Rim Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	166	Silicon hand rim cover, smooth, black ⚠ *NC with cross wheel (C-2466), aluminium push rims (C-494)*	
❑	692	Push rim spacing, narrow	
❑	693	Push rim spacing, wide	

07 Rear Wheels Options

Weight is indicated per item.

	CODE	DESCRIPTION	WEIGHT
❑	697	Release mechanism for tetraplegics, facilitates removal of the drive wheel ⚠ *Only with Silverdesign (C-848) or Active wheel (C-695)*	
❑	489	Hand and spoke guard, transparent	
❑	2082	Spoke reflectors	
❑	819	Reflectors ⚠ *NC with rear wheels C-752, C-2473, C-2461, C-2468, C-2470, C-2471, C-2472*	

08 Camber

	CODE	DESCRIPTION
❑	478	0°
❑	447	3°

09 Center of Gravity

The measurement is taken from the rear edge of the backrest tube to the wheel axle centre, in millimetres.

	ACTIVE			MEDIUM			PASSIVE	
	1 (115mm)	2 (95mm)	3 (75mm)	4 (55mm)	5 (35mm)	6 (15mm)	7 (-5mm)	8 (-25mm)
Position	❑	❑	❑	❑	❑	❑	❑	❑

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

10 Footplates

The difference between the front seat height (FSH) and the lower leg length (LLL) must be at least 50mm.

LLL (mm)	260	270	280	290	300	310	320	330	340	350	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520
A												❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑
B	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑	❑																

	CODE	LLL	DESCRIPTION	WEIGHT
❑	805	A	Two-piece footplates, black plastic, flip-up and height adjustable ⚠ *NC with seat width 320mm (C-32)*	
❑	808	A	Two-piece footplates, black aluminium, flip-up, height/depth and angle adjustable ⚠ *NC with seat width 320mm (C-32)*	
❑	3532	B	High-mounted two-piece footplates, black aluminium, flip-up, height/depth and angle adjustable ⚠ *NC with seat width < 380mm (C-32, C-34, C-36)*	
❑	312	A	One-piece footplate, black aluminium profile, flip-up, height/depth and angle adjustable - Depth: 100mm	
❑	315	A	One-piece footplate, black aluminium, flip-up, height/depth and angle adjustable - Depth: 150mm	

Footplates Accessories

	CODE	DESCRIPTION	WEIGHT
❑	359	Calf strap	
❑	823	Heel loops ⚠ *NC with footplate one-piece (C-312, C-315)*	

11 Backrest

	CODE	DESCRIPTION	WEIGHT
❑		Standard backrest, angle-adjustable	
❑	818	Backrest foldable forward onto the seat ⚠ *NC with backrest height < 400mm* *NC with armrests (C-81, C-84)*	

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Height (RH)

The backrest cover is adjustable with hook-and-loop fasteners, and the back height can be adjusted ±60mm in 15mm increments.

	C-620	C-626	C-631	C-632	C-633	C-637
	250mm	*300mm	350mm	400 mm	450mm	500mm
Backrest height	❑	❑	❑	❑	❑	❑

Backrest Angle

The backrest angle is measured relative to the seat surface: 90° = upright; <90° = tilted forward; >90° = tilted backward.

	Position A	Position B	Position C	Position D	Position E
	80°	85°	90°	95°	100°
Backrest Angle	❑	❑	❑	❑	❑

Backrest Upholstery

	CODE	DESCRIPTION	WEIGHT
❑	235	Textile, black	
❑	292	Mesh fabric, breathable, black	
❑	593	Without backrest cover	

Backrest Upholstery Options

	CODE	DESCRIPTION
❑	2002	Backrest upholstery, 20mm wider
❑	2003	Backrest upholstery, 40mm wider

☐ Please select by ticking the relevant boxes
Standard version: If no other selection is made, the standard version will be delivered.
S Special construction/individual solution o.r. - on request

Backrest Accessories

	CODE	DESCRIPTION	WEIGHT
❑	2032	*ErgoSeat Pro Thoraxpelotten, klein, Paar	

12 Ride® Backs

Please specify the CODE from the RIDE order sheet:

13 Push Handles

	CODE	DESCRIPTION	WEIGHT
❑	411	Without push handles	
❑	413	Push handles, short	
❑	410	Push handles, long	
❑	141	Push handles, swiveling	
❑	502	Height-adjustable push handles, mounted on back tube, steplessly adjustable up to 150mm *NC with backrest height < 350mm (C-620, C-626)* *The maximum achievable height with height-adjustable push handles is HSH + 564mm*	

14 Arm Supports and Arm Pads

Seat width is measured between the side panels (clothes guards, mudguards, or armrests). Seat upholstery width is 15mm narrower than the effective seat width. Example: For a selected seat width of 400mm, the seat upholstery width is 385mm. Backrest width (measured at the bottom of the backrest tubes) corresponds to the seat upholstery width. Weight is indicated per item.

Clothes and Mudguards

	CODE	DESCRIPTION	WEIGHT
❑	304	Clothes guard, carbon, fixed-mounted	
❑	101	Mudguards, plastic, fixed-mounted	*269/361g
❑	783	Mudguards, carbon, fixed-mounted	189/270g
❑	100	Mudguard, aluminium, black with cold-protection insert, fixed-mounted	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Armrests

	CODE	DESCRIPTION	WEIGHT
❑	81	Armrest, short pad, height-adjustable with one-hand operation, swing-up, removable and lockable ⚠ *NC with RSH < 450mm* *NC with clothes and mudguards*	
❑	84	Armrest, long pad, height-adjustable with one-hand operation, swing-up, removable and lockable ⚠ *NC with RSH < 450mm* *NC with clothes and mudguards*	
❑	24	Tubular armrest with foam rubber pad, aluminium black, swing-away (side), removable, height-adjustable (with tools), non-locking	

15 Seat Cushions

Standard hook-and-loop strips are included on the seat upholstery.

	CODE	DESCRIPTION	WEIGHT
❑	560	Seat cushion, 30mm	
❑	561	Seat cushion, 60mm	
❑	7199	Netti Contour, breathable 3D cover	
❑	7195	Seat cushion Netti Precision Active with Easycare+	
❑	7196	Seat cushion Netti Precision Active with Stella+	

Seat Upholstery Options

	CODE	DESCRIPTION	WEIGHT
❑	833	Safety belt (metal buckle)	

16 Ride® Seat Cushions

Please specify the CODE from the RIDE order sheet:

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

17 Brakes

	CODE	DESCRIPTION	WEIGHT
❑	305	Pressure brake (push to lock)	
❑	2595	Light pressure brake, aluminium	
❑	60/650	One-hand pressure brake, left (incl. long brake lever, foldable)	
❑	74/650	One-hand pressure brake, right (incl. long brake lever, foldable)	

Brake Options

	CODE	DESCRIPTION	WEIGHT
❑	986	Brake lever extension ⚠ *Only with pressure brake (C-305)*	

18 Options

Anti-tippers

	CODE	DESCRIPTION	WEIGHT
❑	728	Anti-tippers, pair, swing-away ⚠ *NC with tipping aid (C-309)*	
❑	729	Anti-tipper, left, swing-away ⚠ *NC with tipping aid (C-309, C-4930)*	
❑	730	Anti-tipper, right, swing-away ⚠ *NC with tipping aid (C-309, C-4931)*	

Tipping Aid

	CODE	DESCRIPTION	WEIGHT
❑	309	Tipping aid, pair ⚠ *NC with anti-tippers (C-728, C-729, C-730)*	
❑	4930	Tipping aid, left, swing-away ⚠ *NC with anti-tippers (C-728, C-729)*	
❑	4931	Tipping aid, right, swing-away ⚠ *NC with anti-tippers (C-728, C-730)*	
❑	970	Crutch holder ⚠ *Only with anti-tipper (C-728, C-729, C-730) or tipping-aid (C-309, C-4930, C-4931)*	

☐ Please select by ticking the relevant boxes
S Special construction/individual solution o.r. - on request
Standard version: If no other selection is made, the standard version will be delivered.

Therapy Table

With 24" rear wheels and a rear seat height of less than 470mm, using the therapy table may limit the armrest height.

	CODE	DESCRIPTION	WEIGHT
❑	929	Therapy table, plastic, transparent, attachable to armrests, suitable for seat widths 400–480?mm ⚠ *Only with armrest, long pad (C-84)*	
❑	930	Therapy table, plastic, dark transparent, slides over armrest pads, for defined seat width ⚠ *Only with armrest, long pad (C-84)*	

Xtrends Options

	CODE	DESCRIPTION	WEIGHT
❑	962	Backpack "X-TREME"	
❑	2080	Wheel bag "BLACK WHEEL CASE" ⚠ *Capacity: 2x 24" or 1x 25" or 1x 26"*	
❑	2081	Wheel bag "MEYRA ACTIVE" ⚠ *Capacity: 3x 24" / 25" / 26" (max. 28")*	